COMMERCIAL RELIABILITY NOW AVAILABLE FOR YOUR HOME





BUILT TO LAST

We still make them like we used to. Built to last up to 25 years in the home - 10,400 cycles.

DURABLE

Components include heavy-duty hinge, heavy-duty variable induction drive system, metal trunnion, bearing and driveshaft, with heavy-duty seal and bearing assembly and aluminium pulley.

Three-coat, commercial-grade steel cabinet will look good and last for years to come, whilst interior protects clothes from rust stains and discolouration.

EXTRA CAPACITY

Dryer: Large 198 litre cylinder, means less wrinkles and creases. Large door opening can handle the biggest loads, so you spend less time in the laundry.

Front Load washer: Large 96.8 litre stainless steel tub, constructed for increased washing performance and water extraction, with 180° swing door.

ENERGY EFFICIENT

Dryer: Whisper quiet, superior airflow of 85 litres per second results in faster drying and less wrinkling of clothes.

Front load Washer: Dynamic balancing, Incredible 440 G-force and 1,200 rpm spin speed for optimum water extraction, and a spray rinse for outstanding results and water saving.

COMPACT

All in one, a space saving unit providing ease of operation with excellent wash results.

STACK WASHER DRY

ATEE9AWP433AW01 **MODEL NUMBERS**

(Electric)

ATGE9AWP433AW01

(Gas)

DIMENSIONS (H X W X D) 1986 x 683 x 704 mm

SHIPPING DIMENSIONS (H X W X D) 2032 x 760 x 860 mm

SHIPPING WEIGHT 193 kg

WASHER SPECIFIC

CAPACITY KG 10 kg **DRUM CAPACITY LITRES** 96.8 L SPIN SPEED G-FORCE (RPM) 440 (1200)

MOTOR SIZE KW (HP) Variable Speed Induction

0.67(0.9)

WATER CONSUMPTION PER CYCLE LT 126 L WATER TEMPERATURE SELECTION

Heavy Duty, Normal Eco, **AVAILABLE CYCLES**

Perm Press, Delicate, Rinse & Spin, Spin Only, Whites, Bulky,

Quick & Favourite cycle

WATER PRESSURE KPA(PSI) 140-830 (20-120)

CYCLE INDICATOR LIGHTS Yes

WASH TUB Stainless **OUTER WASH TUB** Stainless

ELECTRICAL REQUIREMENTS 240 V / 50 Hz AC / 1 Ph

(VOLTAGE/HZ/PH)

PRE WASH OPTION **SOAK OPTION** Yes SECOND & THIRD RINSE OPTION Yes **DELAY START OPTION** Yes SIGNAL FINISH OPTION Yes

DRYER SPECIFIC

CAPACITY

QUIET, EFFICIENT BLOWER

DRYER DRUM CAPACITY (LITRES)

DRYER DOOR WIDTH

DRYER MOTOR HORSEPOWER

AVAILABLE CYCLES

AVAILABLE HEAT SOURCES **ELECTRICAL REQUIREMENTS**

(VOLTAGE/HZ/PH)

DRYER BREAKER SIZE

GAS CONSUMPTION MJ

TEMPERATURE SETTINGS

CABINET

CYLINDER FINISH

CYCLE INDICATOR LIGHT END-OF-CYCLE BUZZER

AUTOMATIC DRY CYCLES

SHOE DRYER RACK

GAS INLET CONNECTION

HEATING ELEMENT MULTIPLE VENT OPTIONS

EXHAUST VENT SIZE

AUSTRALIAN GAS APPROVAL

LP CONVERSION KIT

8.2 kg IEC

Yes

198 L

525 mm

1/3 hp

Heavy Duty, Regular,

Perm Press, Delicate, Time Dry, Quick Dry,

Fluff Up & Favourite cycle

Electric or Gas (NG or LP)

240V / 50 Hz AC / 1 Ph

20 (Electric) 10 (Gas) Amps

21.1 MJ (Gas)

4

Galvanised Steel

White Yes

Yes

Yes Optional

(part number 512082)

3/8 NPT

4000 W (Electric)

Yes 102 mm

Yes

Optional



Image, price and information are subject to change without notice.

